

QS5

4.5 Litre Ultrasonic Bath

Ultrawave's **Q-Series** offers outstanding performance for use in scientific and laboratory applications, chiropody, veterinary and many other professional environments.

Incorporating Ultrawave's Frequency Leap Technology, homogenous cavitation activity is generated throughout the ultrasonic bath reducing dead spots and standing waves. This provides a more consistent scrubbing action for excellent results.



The **QS5** is a 4.5 Litre heated, digital ultrasonic bath.

The menu driven control panel allows simple adjustment of cycle time (0 to 99 minutes), temperature (ambient to 70°C), ultrasonic power and frequency mode for precise and accurate processing.

Combining features such as degas mode, fluid level sensor and a memory card port, the **QS5** offers repeatable and traceable cleaning performance with consistent cleaning results every time.



QS5

4.5Litre Ultrasonic Bath

| | |
|------------------------------------------------|---------------------------|
| Construction Case | 304 Stainless Steel |
| Construction Tank | 304 Stainless Steel |
| Front Panel | ABS Plastic |
| Control | Digital LCD |
| Overall Dimensions | 345 x 200 x 265mm (WxDxH) |
| Tank Dimensions | 300 x 150 x 150mm (WxDxH) |
| Basket Dimensions | 275 x 125 x 90mm (WxDxH) |
| Maximum Capacity | 5.0Litres |
| Working Capacity | 4.5Litres |
| Ultrasonic Power | 100W |
| Ultrasonic Power (per Litre) | 22.2W/Litre |
| Operating Frequency | 32 - 38KHz Frequency Leap |
| Maximum Heating Capacity | Ambient - 70°C |
| Heater Power | 150W |
| Timer | 0 - 99 minutes |
| Mains Connection | 220 – 240V (50 - 60Hz) |
| Drain Outlet | 3/8" BSP VALVE |
| Lid | ABS Plastic |
| Basket | Stainless Steel |
| Gross Weight (inc. lid, basket & packaging) | 6.5KGs |
| Net Weight | 5.5KGs |
| Warranty | 3 Years |

