

Lennox introduces the **NEW** high precision RFM300-T Refractometer from Bellingham and Stanley

Update your measuring technique with the latest developments from Bellingham and Stanley.

Latest developments

- Easy to use high clarity 7" High Definition Touchscreen
- Fast and accurate temperature control by Peltier Technology
- Flat prism surface for easy cleaning
- Wide beam scan allows use with non-homogenous samples
- Methods library including PHR-MEAN (Pharmaceutical) and user defined methods
- High precision precise readings (0.001 Brix, 0.000001 RI)

Upgraded Technology - New Software

Allows you to:

- Save over 8000 readings
- Trace configuration of users and reads
- Ensure continued accuracy with user maintenance prompts
- Connect to external keyboard by USB port
- Configure multiple instruments using memory stick
- Use it remotely for handling diagnosis / IQ with free PC software

Try out the new technology in your laboratory with a **FREE** demonstration from our expert team

- Phone 01 455 2201 or Email sales@lennox.ie



Suitable for measurement and control in demanding Pharmaceutical, Food, Beverage, Chemical and Industrial applications.

www.lennox.ie

RFM300-T Series Refractometers

TOUCHSCREEN HIGH PRECISION MODELS WITH PELTIER TEMPERATURE CONTROL
FOR DEMANDING FOOD, BEVERAGE, CHEMICAL & INDUSTRIAL APPLICATIONS



Bellingham + Stanley has been manufacturing refractometers for over a Century and the latest refractometers build on that legacy.

The RFM300-T Series is the latest in a line of RFM models designed specifically for use in harsh environments.

Incorporating wide beam optics and one of the flattest prism platforms on the market, RFM300-T Series refractometers are capable of measuring non-homogenous samples such as fruit juice with pulp, opaque chemical compounds and emulsions that are normally difficult to read with optical refractometers or those digital refractometers that do not address the need to measure "difficult samples."



The new instrument's ABS case is ergonomically designed so that any spills are dealt with by its sloping shape or by the PEEK spill barrier that surrounds the shallow, easy-clean stainless steel prism dish.

Inherent to the modern design is the new high definition, capacitive touchscreen display that not only facilitates use in factory environments, even when operating whilst wearing gloves, but also is the centrepiece of the new software that helps the operator quickly manoeuvre through the user and configuration menus. SMART temperature stability, RFID user clearance and application specific pre-programmed Methods simplify routine analyses within pharmaceutical and petrochemical industries. Supplied PC software enables control via Ethernet connection so that technical support and training may be performed remotely.

- 7" High definition touchscreen display
- Flat prism surface for easy-cleaning
- Wide beam scan for non-homogenous samples
- Three decimal place Brix precision* (6 d.p. RI)
- USP/EP/BP/JP compliant
- Supports FDA regulation 21 CFR Part 11
- PHR-MEAN Method
- USB & Ethernet connectivity

 **Bellingham
+ Stanley**
a xylem brand

RFM300-T Series of high precision refractometers with 7" touchscreen and Peltier temperature control



Specifications	RFM330-T	RFM340-T
Scales		
Refractive Index	1.32 – 1.58	1.32 – 1.58
Sugar (°Brix)	0 – 100	0 – 100
User Defined	100	100
Resolution		
Refractive Index	0.0001	0.000001 (selectable up to 6 d.p.)
Sugar (°Brix)	0.1	0.01 / 0.001 (selectable up to 3 d.p.)
Accuracy		
Refractive Index	± 0.0001	± 0.00002 (1.32 - 1.38 RI) ± 0.00004 (1.38 - 1.58 RI)
Sugar (°Brix)	± 0.1	± 0.010 (0 - 30 °Brix) ± 0.030 (30-100 °Brix)
Precision (Reproducibility)*		
Refractive Index	± 0.00005	± 0.000005 (6 d.p.)
Sugar (°Brix)	± 0.05	± 0.005 (3 d.p.)
User Scale Library	20+ pre-programmed scales including HFCS (3), sugar (4), sucrose SG (3), NaCl, Butyro, Wine Must (5), Urine SG (3), PHR-MEAN and more; plus customer programmable user scales via PC.	
Reading Time	Minimum 4 seconds (dependent on precision required)	
Measuring Temperature Range	0°C or 10°C below ambient whichever is greater to 70°C	
Temperature Sensor Accuracy	± 0.03°C	
Sample Temperature Stability	± 0.05°C	
Temperature Compensation		
Sucrose (°Brix)	5 – 80 °C	
AG Fluid	5 – 40 °C	
User Defined	Simple coefficient (units/°C) or polynomial function	
Temperature Stability Checks	None/delay time/repeatability/Smart (independently selectable by Method)	
Sample Illumination	Light Emitting Diode 589nm (100,000+ hours)	
Prism / Dish	Artificial Sapphire / Stainless Steel 316 / PEEK (spill barrier)	
Prism Seal	Silicone/Resin	
Interfaces	3 x USB (A), 1 x USB (B), 1 x Ethernet, 1 x Serial (RS232)	
Power	Instrument: 24 V DC, ±5%, <2A External PSU: 100-240V, 50-60Hz (supplied)	
Humidity Range	<90% RH (non condensing)	

Order Codes

Code	Description
19-30	RFM330-T Peltier temperature controlled refractometer with latest integral 7" full colour touchscreen, high definition display and USB/LAN connectivity. Supplied with pack of two RFID tags, instruction manual and certificate of conformity.
19-40	RFM340-T high precision Peltier temperature controlled refractometer with latest integral 7" full colour touchscreen, high definition display and USB/LAN connectivity. Supplied with pack of two RFID tags, instruction manual and certificate of conformity.
22-498	Spare filters for RFM-T models (pack of 12)
55-14	Dot-matrix impact printer, 24 column: Serial RS232, 230V (UK/Euro plug)
55-16	Dot-matrix impact printer, 24 column: Serial RS232, 110V (USA plug)
54-02	Serial interface cable for printer

Latest Software Features

- Dual display function Brix/SG
- Save over 8000 readings
- Reading, user & config audit trails
- Print to secure PDF
- Simple USB "Back-up & Clone"
- User maintenance prompts
- Remote diagnostics & control

*for definitions, please visit our website



© 2016 Xylem Inc. All rights reserved. Bellingham + Stanley is a trademark of Xylem Inc. or one of its subsidiaries.

RFM300-T-EN/216