

The Only Pre-Calibrated, Single-Use Pressure Sensors with an On-Board Chip that Stores ALL Calibration and Data Documentation.

How SciLog Sensors Enhance Your Process

- Pre-Calibrated
- NIST-Traceable
- Certified Calibration
- Gamma-stable
- NaOH Stable
- Autoclave Stable
- Comprehensive Customer Support
- Extended-Use Sensors

The SciPres fully integrates & optimizes most existing systems involving...

- Filtration
- Chromatography
- Reverse Osmosis
- Fermentation
- Bags & Manifolds

SciPres Range & Accuracy

- Pressure Range: -5 to 60 psi.
- Pressure Accuracy: ± 0.30 psi.



Durable + Accurate + Scalable + Affordable



Luer



3/8" Barb



1/2" Barb



3/4" Tri-Clover



1" Tri-Clover
"Ladish"

Sensor Specifications

Sterilizability

- Can be Sterilized
 - IPA 70
 - NaOH (0.1N-1.0N)
- Autoclavable (1x)
- Gamma Stable (25-45kGy)

Material, Fluid Contact:

- Medical Grade
- Meets USP Class VI and FDA 21CFR177.1520
- All Wetted Materials are made of Animal-Free Compounds

Sensor Type:

- Medical Grade
- Resistive
- Sensing Element with On-Chip Temperature Compensation

Sensor Microchip:

- EPROM
- Stored Sensor ID and Cal Factor

Sensor Connector & Cables:

- Dust & Water Proof
 - IP67



Monitor Specifications

Sensor Inputs:

- Up to Three Simultaneously

Sensor Readout:

- P1, P2 and P3
- Differential Pressure (DP)
- Transmembrane Pressure (TMP)
- Display of DP and TMP are User-Selectable

Analog Outputs:

- 4-20 mA Outputs for P1, P2, P3, & DP or TMP
- 18 Bit Resolution

Digital Output:

- RS-232

Alarm Outputs:

- 4 TTL Switches
- User-Selectable Hi/Lo Pressure Limit Settings for P1, P2, P3, and DP or TMP

Power Supply:

- 115/230 VAC



scilog.com/scipres
800-955-1995 | email to TSS@scilog.com

Copyright © Scilog 2012. All Rights Reserved Doc #6192012